

Crossbars are removable along both radii Large, rounded crossbars for long cable life

Closed and open styles can be combined

4 Hinged snap-open removable lids along outer radius

4

8

R_[mm] Bending Radii

150

250

063* 075

125

200

Radii for all widths!

Not available for R76

100

175

Optimized glide pads

Part No.


Removable lids along inner radius


MA mounting brackets with attachment points on all sides


Bi [mm] Ba [mm]

3 Mounting brackets available both locking and pivoting

Integrated strain relief possible








(indicate chain-lengths or number of links) 5,0 m (55 links) Series 22.040.150.0

+ 2 separators 2211 assembled each 2nd link


+ 1 set mounting brackets 220.040.12

Series 22 crossbars every link




Series 23 crossbars every 2nd link





Series R76 fully enclosed E-Tube



22/23.040	40	60
22/23/76.050	50	70
22/23.062	62	82
22/23.070	70	90
22/23/76.075	75	095
22/23/76.100	100	120
22/23/76.125	125	145
22/23/76.150	150	170
22/23/76.175	175	195
22/23/76.200	200	220
22/23/76.225	225	245
22/23/76.250	250	270
22/23.275	275	295
22/23/76.300	300	320

Supplement Part No. with required radius. Example: 22.040. 150 .0 Bending radii listed above can be combined with every chain width!